BEST AVAILABLE COPY

New U.S. National Stage of PCT/EP2004/009140

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Original) Coating composition comprising one or more polymer binders cross-linkable by polar reaction and at least one catalyst, the cross-linkable polymer binders being comprised in a liquid phase, characterised in that a separate dry sprinkleable powder phase comprises at least a part of the catalyst and/or of a precursor of the catalyst which forms the catalyst in reaction with a co-reactive compound in the liquid phase.
- (Original) A coating composition according to claim 1, characterised in that at least one catalyst includes a Lewis acid or Lewis base.
- 3. (Currently Amended) A coating composition according to claim 1-or 2, characterised in that the liquid phase comprises a compound which is reactive with a precursor in the powder phase to form a Lewis base or Lewis acid after the liquid phase is exposed to the powder phase.
- 4. (Currently Amended) A coating composition according to any one of the preceding claims claim 1, characterised in that the liquid phase is a two-component composition, the first component comprising one ore more polyisocyanates and the second component comprising a polythiol, polyol, polyamine or mixtures thereof.

BEST AVAILABLE COPY

New U.S. National Stage of PCT/EP2004/009140

- 5. (Currently Amended) A coating composition according to any one of preceding claims 1
 -4 claim 1, characterised in that the liquid phase is a two-component composition, the first component comprising one ore more polyepoxies and the second component comprising one or more polythiols.
- 6. (Currently Amended) A coating composition according to any one of preceding claims 1
 —4 claim 1, characterised in that the liquid phase is a two-component composition, the
 first component comprising a polyunsaturated binder and at least one electronwithdrawing group linked to a carbon atom of at least one of the unsaturated bonds, the
 second component comprising a polythiol and/or a compound comprising acidic CH
 groups.
- 7. (Original) A coating composition according to claim 3, characterised in that the powder phase comprises one or more phosphine compounds and in that the liquid phase comprises one or more electron-deficient olefins.
- 8. (Currently Amended) A coating composition according to any one of preceding claims 1
 6 claim 1, characterised in that the powder phase comprises one or more amines.
- (Currently Amended) A coating composition according to any one of the preceding elaims claim 1, characterised in that the catalyst in the powder phase is a solid material in powder form.

DEST AVAILABLE COPY

New U.S. National Stage of PCT/EP2004/009140

- 10. (Original) A coating composition according to claim 9, characterised in that the powder is zinc oxide, calcium oxide and/or calcium carbonate.
- 11. (Currently Amended) A coating composition according to any one of preceding claims 1
 —8 claim 1, characterised in that the powder comprises a solid carrier material in powder form having one or more of the activating compounds adsorbed to its surface.
- 12. (Original) A coating composition according to claim 11, characterised in that the carrier material is sand, diatomaceous earth, zeolite, vitreous beads, barium sulphate, chalk, pigment, or mixtures thereof.
- 13. (Original) A coating composition according to claim 12, characterised in that the powder material is titanium dioxide coated with a zirconium compound.
- 14. (Original) A coating composition according to claim 12, characterised in that the carrier material comprises a mixture of sand having an average particle size above 200 micrometers and a fine sand having an average particle size below 100 micrometers.
- 15. (Original) A coating composition according to claim 14, characterised in that it comprises more than about 60 wt.% of sand having an average particle size between 300 800 micrometers, 15 30 wt.% of quartz sand having an average particle size of 20 90 micrometers, and a fine grade quartz sand having an average particle size below 10 micrometers, preferably about 3 micrometers.

BEST AVAILABLE COPY

New U.S. National Stage of PCT/EP2004/009140

- 16. (Currently Amended) A coating composition according to any one of the preceding elaims claim 1, characterised in that the powder phase comprises up to about 8 wt.% of the catalyst, preferably up to about 5 wt.%, more preferably up to about 3 wt.%.
- 17. (Original) Method of applying a coating composition comprising in a liquid phase one or more polymer binders cross-linkable by polar reaction and in a separate dry powder phase at least one catalyst wherein after application of one or more layers of the liquid phase on a substrate, the powder phase is sprinkled over the wet liquid phase layer.
- 18. (Original) Method of applying a coating composition comprising in a liquid phase one or more polymer binders cross-linkable by polar reaction and in a separate dry powder phase at least one precursor of a catalyst which forms the catalyst in reaction with a coreactive compound in the liquid phase wherein after application of a layer of the liquid phase on a substrate, the powder phase is sprinkled over the wet liquid phase layer.
- 19. (Currently Amended) A method according to claim 17-or 18, characterised in that the thickness of the freshly applied layer of liquid phase is less than the particle size of at least a part of the powder phase material, and in that after sprinkling the powder phase over the wet liquid phase layer, a second layer of the liquid phase is applied.